

High-Definition **DVB-T/T2 OTT STB**

AS952 Series



- Compliant with MPEG-2,MPEG-4, H.264, H.265, andAVS
- Compatible with HDTV channels and equipped with HDMI connector
- EPG and DVB Teletext
- DVB subtitles
- Auto-search, blind search, and network search functions
- Supports Media Player
- Supports CAS

ACT AS952 Series IP Based High Definition Over-The-Top (OTT) Set-Top Box (STB) is an intelligent subscriber home device designed for the ultimate user experience with support for DVB-T/T2 receivers including multicast, VOD, and internet access.

The AS952 Series STB is equipped with a powerful high-performance dual MIPS media processor in a lightweight modern package that allows for a flexible and personalized viewing experience. The AS952 Series STB provides high quality and robust services with advanced streaming protocols enabling an over the top broadcast experience at a superior quality.

Together with ACT end-to-end HFC and FTTX network solution, the powerful AS952 residential OTT STB equipment enables Network Operators and Services Providers to offer their customers/subscribers with superior Audio and Video experience.



Key Features –

- Compliant with MPEG-2, MPEG-4, H.264, H.265, and AVS
- Compatible with HDTV channels and equipped with HDMI connector
- EPG and DVB Teletext
- DVB subtitles
- Auto-search, blind search, and network search functions
- Supports Media Player
- Supports CAS

Specifications -

Item	Description
Core System	
Processor	M88CS8001 (high-performance dual MIPS CPU)
Broadcast Tuners	1 DVB-T2/T
Memory	8 MB flash
	SOC embedded 64 MB DDR
STB Upgrade	Through OTA or USB disk
Tuner & Demodulator	
Input Frequency	110 MHz to 860 MHz
Demodulator	QPSK, 16QAM, 64QAM, 256QAM, demodulation supported
Channel Bandwidth	5M, 6M, 7M, 8MHz
Video Decoding	MPEG-4 simple profile, advanced simple profile @ level 5 without GMC/data
	partitioning/reversible VLC
	H.265 (M88CC8051T only)
	MPEG-2 MP@HL
	AVS Jizhun profile @ L6.0/4.0/2.0
	H.264 BP (with no ASO/FMO), MP & HP @ L4.1
Audio Decoding	MPEG-1/2 Layer I/II/III
	MPEG-2/4 LC-AAC, MPEG-4 HE-AAC @ Level 4
	Dolby AC3/AC3+ (optional)
HD/SD Video Encoding	
HD Formats	480p, 576p, 720p, 1080i/p
SD Formats	NTSC/PAL/SECAM with VBI slicer
Connectivity	
Video	HDMI v1.4a
RCA	RCA out (CVBS, audio L/R)
USB	1 × USB 2.0 host device
Front Panel	



Display 3 LED indicators

Power Red LED Lock Green LED

Button VOL+, VOL-

Physical Characteristics

Operating Temperature 0 °C to +40 °C Power Consumption Max. 5 W

Voltage 90 V_{AC} to 250 V_{AC} (50/60 Hz) Dimensions (W×D×H) 168 mm × 115 mm × 30 mm

Weight 0.3 kg

Packaging Dimensions (W×D×H) 250 mm × 170 mm × 55 mm

Weight (Including Packaging) 0.4 kg

Proposed Accessories Remote control unit

RCA connect cable OR AAA batteries

AAA batteries

Ordering Information

Product Name Product Description

AS952 OTT STB High-Definition DVB-T/T2 OTT STB



Contact Information





Ascent Communication Technology Ltd

AUSTRALIA

140 William Street, Melbourne Victoria 3000, AUSTRALIA Phone: +61-3-8691 2902

CHINA

Unit 1933, 600 Luban Road 200023, Shanghai CHINA Phone: +86-21-60232616

EUROPE

Pfarrer-Bensheimer-Strasse 7a 55129 Mainz, GERMANY Phone: +49 (0) 6136 926 3246

WEB: www.ascentcomtec.com

HONG KONG SAR

Unit 9, 12th Floor, Wing Tuck Commercial Centre 177 Wing Lok Street, Sheung Wan, HONG KONG Phone: +852-2851 4722

USA

2710 Thomes Ave Cheyenne, WY 82001, USA Phone: +1-203 816 5188

VIETNAM

15 /F TTC Building, Duy Tan Street Cau Giay Dist., Hanoi, VIETNAM Phone: +84 243 795 5917

EMAIL: sales@ascentcomtec.com

Specifications and product availability are subject to change without notice. Copyright © 2019 Ascent Communication Technology Limited. All rights reserved. Ver. ACT_AS952_DVB_T2_OTT_STB_Datasheet_V1a_May_2019