

Air-Cooled Low Noise 10 kW Diesel Generator



ATF Series

- Up to 11 kW power generation
- 76 dB noise level
- Robust and reliable
- IP23 protection grade
- Efficient fuel consumption
- Low operating costs
- Low emissions
- ATS system

Ascent's ATF11000ES 10 kW air-cooled silent diesel generator is cost effective and reliable choice for today's power generation market. It is capable of low noise and efficient power generation, delivering 10 kW of power for a variety of applications such as telecommunications, small offices, hotels, retail outlets, and clinics.

ATF11000ES diesel generators are capable of supplying power even in adverse environmental conditions, and are available for both prime and standby power applications. They are characterized by their quiet operation and robustness, and offer efficient fuel consumption to reduce operating costs while limiting emissions to remain ecologically friendly. The included ATS system allows them to automatically power on in case of power outages to ensure that your premises always have power.



Key Features —

- Up to 11 kW power generation
- 76 dB noise level
- Robust and reliable
- IP23 protection grade
- Efficient fuel consumption
- Low operating costs
- Low emissions
- ATS system

Specifications -

| Item | Description |
|--------------------------------------|---|
| Genset Type | Silent |
| Engine Brand / Model | 290F |
| Alternator Brand / Model | Fsstf / STC-10 |
| Prime Power / Capacity | 10 kW / 12.5 kVA |
| Standby Power / Capacity | 11 kW / 13.75 kVA |
| Frequency / Speed | 50 Hz / 3000 rpm |
| Voltage | 400 V / 230 V |
| Rated Current | 18 A |
| P.F(COS¢) | 1 |
| Dimensions (L \times W \times H) | 1160 mm × 675 mm × 945 mm |
| Net Weight | 300 kg |
| Noise Level | 76 dB |
| Accessories | Battery, exhaust pipe, muffler, breaker |
| Engine Specifications | |
| Engine Brand / Model | 290F |
| No. of Cylinder / Arrangement Mode | 2 / In-line |
| Engine Type | 4-stroke, air-cooled |
| Intake System | Naturally aspirated |
| Bore and Stroke | 90 mm × 90 mm |
| Displacement | 0.954 L |
| Speed Regulation | Mechanical |
| Start System | Electric |
| Cooling System | Forced air cooling |
| Fuel Consumption | 250 g/kW∙h |

10 KW Air-Cooled Diesel Generator



Alternator Specifications

Alternator Brand / Model Voltage Regulation Excitation Mode Protection Grade Insulation Class **ATS Specifications** ATS Brand / Model Function Fsstf / STC-10 AVR automatic voltage regulation Single bearing, brush, self-excited IP23 H

SUYANG / 63A 4P Automatically starts and stops the generator



Control Panel



Ordering Information -

Item ATF11000ES **Description** 10 kW air-cooled silent diesel generator

Contact Information -

Ascent Communication Technology Ltd

AUSTRALIA

140 William Street, Melbourne Victoria 3000, AUSTRALIA Phone: +61-3-8691 2902

CHINA

Unit 1933, 600 Luban Road 200023, Shanghai CHINA Phone: +86-21-60232616

EUROPE

Pfarrer-Bensheimer-Strasse 7a 55129 Mainz, GERMANY Phone: +49 (0) 6136 926 3246

HONG KONG SAR

Unit 9, 12th Floor, Wing Tuck Commercial Centre 177 Wing Lok Street, Sheung Wan, HONG KONG Phone: +852-2851 4722

USA

2710 Thomes Ave, Cheyenne WY 82001, USA Phone: +1-203 816 5188

VIETNAM

15 /F TTC Building, Duy Tan Street, Cau Giay Dist. Hanoi, VIETNAM Phone: +84 243 795 5917

WEB: www.ascentcomtec.com EMAIL: sales@ascentcomtec.com

Specifications and product availability are subject to change without notice. Copyright © 2016 Ascent Communication Technology Limited. All rights reserved. Ver. ACT_ATF11000ES_Datasheet_V1b_Jul_2016