

Air-Cooled Low Noise 15 kW Diesel Generator



ATF Series

- Up to 15 kW power generation
- 76 dB noise level
- Robust and reliable
- IP23 protection grade
- Efficient fuel consumption
- Low operating costs
- Low emissions
- ATS system

Ascent's ATF15000ES 15 kW air-cooled silent diesel generator is cost effective and reliable choice for today's power generation market. It is capable of low noise and efficient power generation, delivering 10 kW of power for a variety of applications such as telecommunications, small offices, hotels, retail outlets, and clinics.

ATF15000ES diesel generators are capable of supplying power even in adverse environmental conditions, and are available for both prime and standby power applications. They are characterized by their quiet operation and robustness, and offer efficient fuel consumption to reduce operating costs while limiting emissions to remain ecologically friendly. The included ATS system allows them to automatically power on in case of power outages to ensure that your premises always have power.



Key Features —

- Up to 15 kW power generation
- 76 dB noise level
- Robust and reliable
- IP23 protection grade
- Efficient fuel consumption
- Low operating costs
- Low emissions
- ATS system

Specifications -

Item	Description
Genset Type	Silent
Engine Brand / Model	Beinei Deutz / F2L912
Alternator Brand / Model	Fsstf / STC-15 / Guangdong
Prime Power / Capacity	15 kW / 18.75 kVA
Frequency / Speed	50 Hz / 1500 rpm
Voltage	400 V / 230 V
Rated Current	27 A
P.F(COS¢)	0.8 Lag
Dimensions (L \times W \times H)	2050 mm × 900 mm × 1100 mm
Net Weight	800 kg
Noise Level	80 dB
Accessories	Battery, exhaust pipe, muffler, breaker
Engine Specifications	
Engine Brand / Model	Beinei Deutz / F2L912
No. of Cylinder / Arrangement Mode	2-cylinder / In-line
Engine Type	Air-cooled
Intake System	Naturally aspirated
Bore and Stroke	100 mm × 120 mm
Displacement	1.88 L
Speed Regulation	Mechanical
Start System	12 V DC
Cooling System	Forced water cooling
Fuel Consumption	200 g/kW·h

15 kW Air-Cooled Diesel Generator



Alternator Specifications

Alternator Brand / Model Voltage Regulation Excitation Mode Protection Grade Insulation Class **Controller Specifications** Controller Brand/Model: Screen: Language: Type: Operation: Function:

ATS Specifications

ATS Brand / Model Function Fsstf / STC-15 AVR automatic voltage regulation Single bearing, brush, self-excited IP23 H

Smartgen 6120 LCD display Chinese / English / Spanish / Russian AMF automatic operation Automatic start and auto mains (utility) failure control Data measurement and protective alarm, etc. please refer to control system's manual for details.

SUYANG / 63A 4P Automatically starts and stops the generator



Control Panel



ATS Automatic Transfer Switch



Ordering Information -

Item ATF15000ES **Description** 15 kW air-cooled silent diesel generator

Contact Information

Ascent Communication Technology Ltd

AUSTRALIA

140 William Street, Melbourne Victoria 3000, AUSTRALIA Phone: +61-3-8691 2902

CHINA

Unit 1933, 600 Luban Road 200023, Shanghai CHINA Phone: +86-21-60232616

EUROPE

Pfarrer-Bensheimer-Strasse 7a 55129 Mainz, GERMANY Phone: +49 (0) 6136 926 3246

HONG KONG SAR

Unit 9, 12th Floor, Wing Tuck Commercial Centre 177 Wing Lok Street, Sheung Wan, HONG KONG Phone: +852-2851 4722

USA

2710 Thomes Ave, Cheyenne WY 82001, USA Phone: +1-203 816 5188

VIETNAM

15 /F TTC Building, Duy Tan Street, Cau Giay Dist. Hanoi, VIETNAM Phone: +84 243 795 5917

WEB: <u>www.ascentcomtec.com</u> EMAIL: <u>sales@ascentcomtec.com</u>

Specifications and product availability are subject to change without notice. Copyright © 2016 Ascent Communication Technology Limited. All rights reserved. Ver. ACT_ATF15000ES_Datasheet_V1b_Jul_2016