

Smart Contact Sensor

A-SCS-MT02-A0



- Communication Mode: IEEE 802.15.4 (ZigBee/SmartRoom).
- As a security device, once it is opened illegally, preset alarm devices will be triggered, and send alarm message to phone.
- As a trigger device, it can be linked to turn on the lights, play background music and so on.
- Remote monitor the opening/closing state of door/window.
- Alarm in wireless way, strong anti-interference ability.

As a security device, once it is opened illegally, preset alarm devices will be triggered, and send alarm message to phone.

It widely applies to smart community, hotel apartment and office, convenient and safe.

Specifications

Specifications	
Power Parameter	DC 3V
Battery Type	CR2 battery
Standby Current	4 μ A
Door Opening/Closing Current	1.2 μ A at opening, 4 μ A at closing
Alarm Distance	20 mm
Operating Temperature	-10 °C to +45 °C
Operating Humidity	≤95 % RH (non-condensing)
Installation Method	Fixed by screws
Dimensions	Body: 63*23*21 (mm) Magnetic Parts 63*10*15 (mm)
Net Weight	35 g
Gross Weight	80 g

Ordering Information

Item	Description
A-SCS-MT02-A0	Smart Contact Sensor

Contact Information



Ascent Communication Technology Ltd

AUSTRALIA

140 William Street, Melbourne
Victoria 3000, AUSTRALIA
Phone: +61-3-8691 2902

HONG KONG SAR

Unit 9, 12th Floor, Wing Tuck Commercial Centre
177 Wing Lok Street, Sheung Wan, HONG
Phone: +852-2851 4722

CHINA

Unit 1933, 600 Luban Road
200023, Shanghai CHINA
Phone: +86-21-60232616

USA

2710 Thomes Ave, Cheyenne
WY 82001, USA
Phone: +1-203 816 5188

EUROPE

Pfarrer-Bensheimer-Strasse 7a
55129 Mainz, GERMANY
Phone: +49 (0) 6136 926 3246

VIETNAM

15 /F TTC Building, Duy Tan Street, Cau Giay
Hanoi, VIETNAM
Phone: +84 243 795 5917

WEB: www.ascentcomtec.com

EMAIL: sales@ascentcomtec.com

Specifications and product availability are subject to change without notice.

Copyright © 2019 Ascent Communication Technology Limited. All rights reserved.

Ver. ACT_LIMA_Smart_Contact_Sensor_Datasheet_V1a_Mar_2019